


FlexiShield

Paint Protection Film

www.FlexiShield.com



FlexiShield Solar Control Window Films

are designed to enhance comfort and energy efficiency across automotive, marine, and architectural applications.

For automotive use, the films reduce heat, glare, and UV exposure, improving interior comfort and protecting interior finishings against fading.

In marine applications, the films provide sun protection, reduce cabin heat and air conditioning-related fuel consumption, and protect passengers and interiors from UV damage.

For architectural use, FlexiShield films block solar heat, lower cooling costs, and minimize glare, creating a more comfortable indoor environment while significantly reducing the need for energy-consuming mechanical cooling.

FlexiShield offers a range of ceramic, metallic, dyed, and hybrid window film technologies to perfectly match every application and climate requirement.

Series

GT

Carbon Ceramic

COVERAGE YOU CAN COUNT ON!

A brand of:



FlexiShield GT Series

Carbon Ceramic

Keeps your interior cool and private while blocking heat

Carbon ceramic window films offer superior heat rejection, reducing interior temperatures and enhancing comfort. They block harmful UV rays, protecting furnishings and skin.



Nano-carbon technology with a distinct carbon color and impressive performance,



Excellent IR protection (74% to 80%) and 99% UV rejection.



Invulnerable to color fading or shade changes due to its color-stable composition.



Non-metallic construction for a zero-interference protection layer which does not affect cell-phone, radio, and GPS signals.



Energy-saving and cost-effective, for a comfortable and safe driving experience.

These films also provide increased privacy, glare reduction, and improved aesthetics without compromising visibility. Additionally, they are durable and require minimal maintenance for long-lasting performance.

1,5mil 2ply
VLT's 05 to 80.
Life-time warranty.

GT specifications	GT-80	GT-50	GT-40	GT-30	GT-20	GT-10	GT-05
Thickness	2.0mil	1.5mil	1.5mil	1.5mil	1.5mil	1.5mil	1.5mil
Visible Light Transmission	78%	50%	41%	31%	21%	12%	6%
Visible Light Reflection Exterior / Interior	6% / 6%	6% / 6%	6% / 6%	6% / 6%	6% / 6%	5% / 6%	5% / 5%
Infra-Red Rejection	80%	76%	76%	74%	74%	77%	75%
UV Rejection	99%	99%	99%	99%	99%	99%	99%
Glare Reduction	21%	41%	52%	63%	71%	87%	93%
Total Solar Energy Rejection	46%	48%	51%	55%	58%	63%	66%

FlexiShield USA HQ & Manufacturing

+1 (866) 312 9909

FlexiShield EU Distribution Office

+31 6 3458 3582

FlexiShield ME Distribution Office

+971 50 555 4246

www.FlexiShieldUSA.com
contact@reflekttech.com
280 N Roosevelt Ave
Chandler AZ 85226 USA

www.FlexiShieldEU.com
salesEU@reflekttech.com
Marconistraat 70H
Gouda 2809PE NL

www.FlexiShieldME.com
salesME@reflekttech.com
WH 36/D 06 ABA Avenue
Al Qouz 02, Dubai, UAE



100% US manufactured,
developed and tested under the
blazing Arizona sun.

